



## Specification

f<sub>L</sub> f<sub>Y</sub> L ..... %>\*- 26. 7GHz  
 f<sub>L</sub> `U[ Y L ..... FBP/FBE/FBM  
 f<sub>L</sub> GKF L ..... 1. 25  
 f<sub>L</sub> @ L ..... 0. 4dB  
 f<sub>L</sub> cbbW Mcf L ?&" - &#OG&" ( /APC3. 5/SMA  
 f<sub>L</sub> AuhYf] U L ..... # 71 #5  
 f<sub>L</sub> K L ..... &SK  
 f<sub>L</sub> cUh] b[ L .....  
 ....

Cu gilding  
 Cu passivation  
 Al oxidation

## Model selected

|         |   |
|---------|---|
|         |   |
| K2. 92  | K |
| OS2. 4  | O |
| APC3. 5 | A |
| SMA     | S |

XB-WA42 — [ ] — [ ] —

|   |     |
|---|-----|
|   |     |
| P | FBP |
| E | FBE |
| M | FBM |

[ ] — [ ] — [ ] —

|    |  |
|----|--|
|    |  |
| Cu |  |
| Al |  |

|   |        |
|---|--------|
|   | W cf   |
| L | V i Y  |
| G | [fYYb  |
| W | k\] hY |
| B | V UW   |
| H | [fUm   |

|   |                   |
|---|-------------------|
|   | WUh] b[           |
| A | 71 [ ] Xb[        |
| P | 71 dUgg] j Uh] cb |
| O | 5 cl ] XUh] cb    |

## Instruction

Blue boxes are must required fields.  
Shadow boxes aren't option, randomly selected according to inventory.

Beijing Xibao Electronic Technology Co.,Ltd

fIKF( &#6>&SL  
Waveguide to Coaxial Adapter(WA42/BJ220)

www.beijingxibao.com  
010-62312909 62327421